

ARB MODEL NUMBER	VOLTAGE	CURRENT DRAW NO-LOAD	AIR FLOW UNDER NO-LOAD		CURRENT DRAW UNDER LOAD	AIR FLOW UNDER LOAD		WEIGHT -compressor & included accessories		DUTY CYCLE % @ 22°C [72°F] (on time / off time)	SIZE mm [inches] -when positioned vertically in the mounting bracket. -portable compressor sizes shown as carry case size.			AUTOMOTIVE LOAD PROTECTION IN LOOM	AIR LOCKER SOLENOID MOUNTING MANIFOLD	PRESSURE CUTOFF SWITCH	DURABLE POLYPROPYLENE CARRY CASE	AIR FILTER	6 METER [20 FT] TYRE INFLATION HOSE	QUALITY VDO TYRE PRESSURE GAUGE
			@ 0KPa	@ 0PSI		@ 200KPa	@ 29PSI	Kgs	Lbs		HEIGHT	LENGTH	WIDTH							
CKSA12	12	5A	25.0L/m	0.88CFM	6.5A	13.4L/m	0.47CFM	2.4	5.3	35% 21/39	122mm [4.8"]	162mm [6.4"]	88mm [3.5"]	NO	YES	YES	NO	YES	NO	NO
RDCKA	12	13A	36.0L/m	1.27CFM	18A	28.0L/m	1.00CFM	4.3	9.5	25% 15/45	176mm [6.9"]	170mm [6.7"]	90mm [3.5"]	YES	YES	YES	NO	YES	NO	NO
RDCKA24	24	7A	---	---	12A	---	---	4.3	9.5	25% 15/45	176mm [6.9"]	170mm [6.7"]	90mm [3.5"]	YES	YES	YES	NO	YES	NO	NO
RDCPA	12	13A	36.0L/m	1.27CFM	18A	28.0L/m	1.00CFM	6.1	13.4	25% 15/45	208mm [8.19"]	440mm [17.32"]	238mm [9.37"]	NO	NO	NO	YES	YES	YES	NO